

WALL LIGHTS SPECIFICATION SHEET



WL070RGBW

Up / down LED colour change wall light (24W max.)

FEATURES

IP rating	IP65
Colour flexibility	RGBW
Tilttable	No
Input	350mA
LED Lifetime	50,000h L50 B50

INSTALLATION INFORMATION

Bathroom zone	1
Construction Material	Anodised aluminium
Weight	0.9kg
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
WL070RGBW	Silver	6	White	45°	200 / 200	67	154 / 154
WL070RGBW	Silver	4.0	Red	45°	145 / 145	73	60 / 60
WL070RGBW	Silver	6.0	Green	45°	230 / 230	77	168 / 168
WL070RGBW	Silver	6.0	Blue	45°	38 / 38	13	1 / 1

WIRING INFORMATION

Cable / Flying Lead	1x 5-core ribbon cable
Type of Wiring Required	Series

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PR3011	220-240V	Yes	No	1	1	1

ACCESSORIES

LEDRGBWEXT	Colour change Plug & Play 1m extension lead
------------	---



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

@collingwoodLED

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

Complete with wall fixings for easy installation

Projects light in two directions

Separate white LED for permanent use

Full RGBW colour range

Anodised aluminium for use in outdoor and indoor environments

Compatible with a large range of controllers

Beam angle: 45°

