

POND LIGHTS SPECIFICATION SHEET



UL010RGBW

Colour change LED light (5W max.)

FEATURES

| | |
|--------------------|-----------------|
| IP rating | IP68 |
| Colour flexibility | RGBW |
| Tilttable | 360° |
| Rotation angle | 360° |
| Input | 350mA |
| LED Lifetime | 50,000h L50 B50 |
| CRI | >80Ra |

INSTALLATION INFORMATION

| | |
|-----------------------------|-----------------------|
| Bathroom zone | 1 |
| Construction Material | Stainless steel (316) |
| Weight | 700g |
| Maximum ambient temperature | 35°C |
| Electric Class (1, 2, 3) | 3 |

PHOTOMETRICS @ 25°C

| Product code | Wattage | Colour | Beam angle | lm | lm/W | lx @ 1m |
|--------------|---------|--------|------------|----|------|---------|
| UL010RGBW | 1.1 | White | 40° | 50 | 45 | 101 |
| UL010RGBW | 1 | Red | 40° | 38 | 38 | 75 |
| UL010RGBW | 1.1 | Green | 40° | 63 | 57 | 124 |
| UL010RGBW | 1.1 | Blue | 40° | 11 | 8 | 17 |

WIRING INFORMATION

| | |
|-------------------------|---|
| Cable / Flying Lead | 2x 1m CR575RGBW (outside diameter: 7.4mm) |
| Type of Wiring Required | Series |

LED DRIVER

| Product code | Input | SELV | Dimming | Bathroom zone | Min | Max |
|--------------|-------|------|---------|---------------|-----|-----|
| PR3011 | N/A | Yes | Yes | 1 | 1 | 6 |

ACCESSORIES

| | |
|-----------|------------------------------|
| JB7 | 5-pole IP68 inline connector |
| CR575RGBW | 5-core PVC cable |



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

- Complete with wall fixings for easy installation
- Can rotate and be angled to direct light
- Separate white LED for permanent use
- Full RGBW colour range
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments

Beam angle: 40°

